

For application, processing and cleaning of the ASLAN ReApply series

Thank you for choosing our high quality films

These adaptable products from the ASLAN ReApply series are produced using a combination of the world renowned ASLAN memoboard films. They are equipped with a revolutionary adhesive system and can be easily attached to smooth and slightly textured surfaces, transforming them into a useful communication area. They can then be simply removed for use another time without affecting the room's overall decor.

The reusable ASLAN ReApply series offers the following combinations:

With a quality ferro layer for use with magnets.

ReApply FerroWhiteboard ASLAN RA 650 	magnet receptive gloss whiteboard film
ReApply FerroWhiteboard Matt ASLAN RA 690	magnet receptive matt whiteboard film
ReApply FerroBlackboard ASLAN RA 640	magnet receptive matt blackboard film

Without the ferro layer for easy of use

ReApply Whiteboard ASLAN RA 695	gloss whiteboard film
ReApply Whiteboard Matt ASLAN RA 675	matt whiteboard film

General Application Instructions

The ASLAN ReApply series will adhere to a variety of smooth and slightly structured surfaces such as glass, plexi, acrylic, metal, steel, aluminum, melamine resin panels, wood, veneer and plastic.

The strength of the adhesion is dependant on the surface of the substrate. If this is smooth and shiny, the film can be applied dry by hand or with a cloth. Due to the unique adhesive system, this will immediately create a long lasting bond. Adhesion can also be achieved on low-energy surfaces.

On substrates where ASLAN ReApply does not develop sufficient adhesion, e.g. matt and slightly textured surfaces, adhesion can be improved with the application of water. It is recommended that the surface of the substrate is moistened sparingly using a spray bottle or damp cloth. The ASLAN ReApply should then be applied with pressure using a squeegee or cloth. Only a small amount of water is recommended. Too much water could lead to foam residues, however this can easily be removed. Before application, please check the substrate for water resistance.

The ReApply series can easily be removed at any time. With long-term use, there is no increase in adhesion or the risk of residues left after removal.

For application, processing and cleaning of the ASLAN ReApply series

General Information on Processing

The films of the ReApply series can be cut into a wide variety of shapes. We recommend the use of a plotter cutter or router. When using a plotter cutter, the ReApply should be cut with the top side facing down in order to prevent tunnelling. Due to the slight tackiness of the ferro base material, it cannot be guided over fixed rollers or surfaces. The PVC-free solution ASLAN RA 650 can be cut with a laser cutter.

For the manufacture of short rolls, the products from the ReApply series can be processed by hand or using rewinding machines. To prevent the ferro base material from sticking to the rewinding rollers, it is recommended to wrap the roller in application tape (e.g. LowTackTape ASLAN TP 110).

The product should not be folded or bent during transport or use, as this could lead to permanent damage to the writing surface. Sometimes small dents or pressure points occur during handling and marks may be visible when magnets are removed. However, these will work their way out over a period of time. Raised corners can be relaxed and brought back flat again by heating with a heat gun or hairdryer.

After use the dry film can be rolled up, stored and reused. For storage and transportation, the material should be rolled up on a core (3") with the top surface facing outwards (ferro base inwards). To avoid possible pressure points, we recommend storing the roll on its end – do not lay down or stack.

If dust has collected on the back of the functional film after repeated use, it can simply be removed with a damp cloth; this will not harm the adhesive system.

For application, processing and cleaning of the ASLAN ReApply series

General information on Writability and Cleaning

The ReApply series can be written on with all commercially available whiteboard markers (whiteboard surfaces ASLAN RA 650, RA 690, RA 695, RA 675) or normal blackboard chalk and liquid chalk pens (blackboard surface ASLAN RA 640). A damp microfiber cloth is recommended for easy removal of text. If you accidentally use unsuitable pens, such as permanent markers, the film can be cleaned with alcohol or mineral spirits without leaving any residue.

We do not recommend an application of our ReApply functional films with mounting tapes or other self-adhesive materials. The writable surface of the film can be damaged by taking off the tape so removability cannot be guaranteed anymore.

If you have any questions about special applications, please speak to our technical department: +49 2204 70880

Stand 10 | 2021

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test the suitability of our products for the intended purpose.

The quality of our products is regularly examined, upgraded and developed. We therefore reserve the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of our products in accordance with our latest knowledge.