

CHANGING ADS ON PVC

SignTack Removable ASLAN DFP 13G

CLEAN REMOVABLE FROM PVC SUBSTRATES



ADVANTAGES

- ➔ White matt film
- ➔ Removes clean for minimum three months from PVC substrates
- ➔ Adheres safely and withstands different weather conditions
- ➔ For hanging, sticking or tensioned PVC materials, printed and unprinted
- ➔ Low initial tack of 0.4 N/25 mm allows easy repositioning
- ➔ Grey adhesive ensures high opacity
- ➔ Printable using (eco-)solvent, latex and UV curable inks

The easy solution for temporary promotional messages on PVC surfaces: With the white matt digital printing film **SignTack Removable ASLAN DFP 13G**, temporary promotional messages can be applied to PVC surfaces and, thanks to a special adhesive technology, can also be easily removed.

The combination of the strong adhesion of **SignTack Removable ASLAN DFP 13G** on PVC surfaces, even under challenging weather conditions, and the residue-free removal for at least three months makes this film the only reliable choice for recurring events or temporary information on:

- ➔ Vinyl & laminates (monomeric, polymeric, and cast), glossy & matt
- ➔ PVC banners (cast, laminated, semi-coated)

The grey adhesive also ensures high opacity, preventing the surface from showing through the print.



CHARACTERISTICS

SignTack Removable ASLAN DFP 13G

	FACE FILM	PVC, monomeric
	THICKNESS	80 µm
	ADHESIVE	Removable
	PRINTABILITY	(Eco-)solvent, latex and UV curable inks
	SURFACE	PVC
	CLEAN REMOVABILITY	3 months
	DIMENSIONS	1.37 m x 50 m


APPLICATION

Developed for temporary applications on PVC surfaces. It is used for updating information and placing promotional messages without damaging the print on PVC banners or self-adhesive PVC films.

- ➔ On PVC films (printed or unprinted), e.g. wrapped buses, taxis, vehicles, billboards, signage
- ➔ On PVC banners such as frontlit & blockout banners, e.g. on construction fences, in retail, at events, at sports venues
- ➔ On glass decoration films on shop windows, e.g. for grand openings

TIPS & TRICKS

- ➔ Allow **SignTack Removable** ASLAN DFP 13G to outgas for 48 hours after printing before applying the film to PVC surfaces.
- ➔ Deviation from intended use: When used on polypropylene or polyethylene, e.g. roll-ups, the final adhesive strength is very low (PE = 3 N/25 mm, PP = 5 N/25 mm).



WANT TO KNOW MORE?

Order your samples on
www.aslanfolien.de

Please contact us

Fon +49 2204 708 80

E-Mail info@aslanfolien.de

For more information please visit
www.aslanfolien.de



ASLAN Selbstklebefolien GmbH | Oberauel 2 | 51491 Overath | Germany

ASLAN[®]
EXPERTISE IN SELF-ADHESIVE FILMS