## MultiStitch Embroidery ASLAN ME 70

## Embroidering non-woven in black or white

Self-adhesive non-woven material in black or white, which is perfect for machine embroidery. Even sensitive fabrics or small objects that cannot be fixed in the hoop, can be embroidered by using MultiStitch Embroidery. Optimal adhesive force avoids material's slipping while embroidering and after the embroidery process only the used area of the non-woven has to be removed – of course residue-free.

For any further information please contact our technical advisory service: +49 2204 70880

$\sim$	_	 - 1	t		ct		
1.0	u j	 -		ш		II U. J	,,,,

Face film: PET/CV non-woven

Film weight: 50 g/m<sup>2</sup>

Adhesive: Pressure sensitive polyacrylate adhesive, Square quantity: ~ 15 g/m²

removable

Release liner: Silicone paper Square weight: ~ 85 g/m²

Characteristics

Adhesive strength (ASTMD-903): immediately: ~ 2.5 N/25 mm

Temperature: Application temperature: min. 15 °C

Service temperature range: -30 °C up to +80 °C

Storage: Before application the film can be stored for minimum 2 years from date of production. The

film must be stored at room temperature (15-25 °C) and a relative humidity of the air of 50-60%. To avoid pressure points appearing on the roll surface, we recommend the rolls be

stored either vertical standing or for this purpose designed 'hanging' racks.

State 11|2019 All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test the suitability of our

believe to be reliable. It remains the customer's responsibility to test the suitability of our products for the intended purpose.

The quality of our products is regularly examined, upgraded and developed. We take the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical

characteristics of our products in accordance with our latest knowledge.



