

# TransferLiquid ASLAN TL 10

## Transfer liquid for effective wet application

TransferLiquid ASLAN TL 10 is a transfer liquid for effective wet application of ASLAN self-adhesive films. The ASLAN TL 10 concentrate is available in 0.5 litre bottles. It comes with an empty spray bottle and needs diluting in a ratio of 1:10 with water.

For additional information please contact our technical advisory service:  
**+49 22 04. 7 08-80**

---

## Chemical characteristics

Non-flammable, aqueous solution from anionic and non-ionic surfactants and alcohols.  
No requirement to label  
An EEC safety document is available.

---

## First aid measures

In case of eye contact, thoroughly rinse with cold water.

---

## Processing

Before application, thoroughly clean the surface and evenly wet it with diluted TransferLiquid ASLAN TL 10. Align the self-adhesive film with the application tape on the wet surface, apply the film onto the substrate using a squeegee and push out the liquid completely with firm pressure. Carefully remove the application tape in an angle of 180° and wipe up any remaining fluid with a soft, absorbent cloth. A whitening of the adhesive can occur, but will disappear after a couple of days depending on the weather conditions.

---

**State: 03|2018**

All technical data and advice is based on our experience and measured testing that we believe to be reliable. It remains the customer's responsibility to test the suitability of our products for the intended purpose.

The quality of our products is regularly examined, upgraded and developed. We take the right, without prior notice, to adjust, upgrade and improve the chemical structures or physical characteristics of our products in accordance with our latest knowledge.

---

**ASLAN, Schwarz GmbH & Co. KG**

Oberauel 2 · 51491 Overath · Germany

**phone** +49 (0) 2204.708 80 · **fax** +49 (0) 2204.708 50

**e-mail** info@ASLAN-Schwarz.com



**www.ASLAN-Schwarz.com**

**ASLAN**®

EXPERTISE IN SELF-ADHESIVE FILMS